

SILK Transformer Volume Attenuator

SECONDARY

Tap	Wire color	Heat Shrink tube color	0 dB connection	+6 dB connection
23	RED	RED	0.0	+6.0
22	BRN	RED	-3.0	+3.0
21	BLK	RED	-6.0	+0.0
20	WHT	YEL	-8.0	-2.0
19	GRY	YEL	-9.5	-3.5
18	VIO	YEL	-11.0	-5.0
17	BLU	YEL	-12.5	-6.5
16	GRN	YEL	-14.0	-8.0
15	YEL	YEL	-15.5	-9.5
14	ORG	YEL	-17.0	-11.0
13	RED	YEL	-18.5	-12.5
12	BRN	YEL	-20.0	-14.0
11	BLK	YEL	-21.5	-15.5
10	WHT	X	-23.0	-17.0
9	GRY	X	-24.5	-18.5
8	VIO	X	-26.0	-20.0
7	BLU	X	-28.0	-22.0
6	GRN	X	-30.0	-24.0
5	YEL	X	-32.0	-26.0
4	ORG	X	-34.0	-28.0
3	RED	X	-40.0	-34.0
2	BRN	X	-46.0	-40.0
1	BLK	X	Common	
External Shield (Copper wire with cloth tube)				

Internal Screen (GRN wire with YEL strip)		
	Wire color	Heat shrink tube color
Primary 1	BLU	BLK
	RED	BLK
Primary 2	GRN	BLK
	YEL	BLK

